## IN THE CLAIMS

Please amend the claims as follows:

1-8. (Canceled)

range of 300 nm to 600 nm.

- 9. (Previously Presented) A holographic recording medium comprising: a recording layer in which information is to be holographically recorded; and a light-shielding layer which faces a main surface of the recording layer and selectively transmits a recording light, wherein a ratio of a first average transmittance to a second average transmittance is 15 or larger, the first average transmittance being an average transmittance of the light-shielding layer within a wavelength range of λ<sub>rec</sub> 10 nm to λ<sub>rec</sub> + 10 nm where λ<sub>rec</sub> representing a wavelength of the recording light, and the second average transmittance being an average transmittance of the light-shielding layer within a wavelength
- 10.(Original) The medium according to claim 9, wherein the light-shielding layer contains a transparent material and at least one component selected from the group consisting of a dye dissolved or dispersed in the transparent material, metal particles dispersed in the transparent material, and semiconductor particles dispersed in the transparent material.
- 11. (Previously Presented) A holographic recording medium comprising:
  a recording layer in which information is to be holographically recorded; and
  a light-shielding layer which faces a main surface of the recording layer and
  selectively transmits a recording light, wherein the light-shielding layer includes a laminate
  of dielectric layers, materials of the dielectric layers adjacent to each other being different
  from each other.
  - 12. (Canceled)
- 13.( Previously Presented) The medium according to claim 9, wherein the light-shielding layer contains a transparent material and at least one component selected from the group consisting of a dye dissolved or dispersed in the transparent material, metal

Application No. 10/773,323 Reply to Office Action of May 2, 2007

particles dispersed in the transparent material, and semiconductor particles dispersed in the

transparent material.

14.( Previously Presented) The medium according to claim 9, wherein the

light-shielding layer includes a laminate of dielectric layers, materials of the dielectric layers

adjacent to each other being different from each other.

15. (Original) The medium according to claim 9, wherein the recording layer contains

organic material.

16. (Original) The medium according to claim 9, wherein the recording layer contains

inorganic material.

17.(Original) The medium according to claim 9, further comprising a substrate which

supports the recording layer and the light-shielding layer with the recording layer interposed

between the substrate and the light-shielding layer.

18.(Original) The medium according to claim 9, further comprising a reflecting layer

which is disposed on a side of the recording layer opposite to the light-shielding layer.

19. (Original) The medium according to claim 18, further comprising a substrate

between the recording layer and the reflecting layer.

20. (Canceled)

3